


RI-10S10C-CA600-H1151

Incremental Shaft Encoder

Industrial Line




Technical data

Type	RI-10S10C-CA600-H1151
ID	200018040
Measuring principle	Optical
General data	
Max. rotational speed	6000 rpm
Moment of inertia of the rotor	$1.8 \times 10^{-6} \text{ kgm}^2$
Starting torque	$< 0.05 \text{ Nm}$
Output type	Incremental
Resolution, incremental	600 ppr
Electrical data	
Operating voltage U_B	5...30 VDC
No-load current	$\leq 90 \text{ mA}$
Output current	$\leq 20 \text{ mA}$
Short-circuit protection	yes
Wire break/reverse polarity protection	no
Pulse frequency max.	300 kHz
Signal level high	min. 2.5 V
Signal level low	max. 0.5 V
Output function	5-wire, RS422, with inverted signals
Mechanical data	
Flange type	Clamping flange
Flange diameter	$\varnothing 58 \text{ mm}$
Shaft Type	Solid shaft

Features

- Clamping flange, $\varnothing 58 \text{ mm}$
- Solid shaft, $\varnothing 10 \text{ mm} \times 20 \text{ mm}$
- Optical measuring principle
- Shaft material: stainless steel
- Protection class IP67 on housing and shaft side
- $-40 \dots +85 \text{ }^\circ\text{C}$
- Max. 6000 rpm (continuous operation 3000 rpm)
- 5...30 VDC
- Male connector, M12 x 1, 5-pole
- Open collector (7273)
- Pulse frequency max. 300 kHz
- 600 pulses per revolution









1	GND
2	U_B +
3	A
4	A inv.
5	B
6	B inv.
7	0
8	0 inv.
PH	shield



Technical data

Shaft diameter D (mm)	10
Shaft diameter D	0.394 in
Shaft Length L [mm]	20
Shaft length (L)	0.787 in
Shaft material	Stainless steel
Housing material	Die-cast zinc
Electrical connection	Connector, M12 × 1
	8-pin
Axial shaft load	50 N
Radial shaft load	100 N
Environmental conditions	
Ambient temperature	-40...+85 °C
Vibration resistance (EN 60068-2-6)	300 m/s ² , 10...2000 Hz
Shock resistance (EN 60068-2-27)	3000 m/s ² , 6 ms
Protection class	IP67
Protection class shaft	IP67


Accessories

RA-BC-20-06-10  Bellows coupling with aluminum hub Ø 20 mm; d1 = 6 mm, d2 = 10 mm	100048779	RA-BC-20-08-10  Bellows coupling with aluminum hub Ø 20 mm; d1 = 8 mm, d2 = 10 mm	100048781
RA-BC-20-10-10  Bellows coupling with aluminum hub Ø 20 mm; d1 = 10 mm, d2 = 10 mm	100048782	RA-BC-20-10-12  Bellows coupling with aluminum hub Ø 20 mm; d1 = 10 mm, d2 = 12 mm	100048783
RA-BC-E-20-06-10  Stainless steel bellows coupling Ø 20 mm; d1 = 6 mm, d2 = 10 mm	100048786	RA-BC-E-20-10-10  Stainless steel bellows coupling Ø 20 mm; d1 = 10 mm, d2 = 10 mm	100048787
RA-BC-E-20-10-12  Stainless steel bellows coupling Ø 20 mm; d1 = 10 mm, d2 = 12 mm	100048788	RA-SDC-30-10-10  Spring disc coupling Ø 30 mm; d1 = 10 mm, d2 = 10 mm	100048792

RA-SDC-30-10-12

100048793


Spring disc coupling Ø 30 mm; d1 = 10 mm, d2 = 12 mm



RA-HC-25-10-12

100048797


Aluminum helix coupling Ø 25 mm; d1 = 10 mm, d2 = 12 mm



RA-HC-25-10-10

100048796


Aluminum helix coupling Ø 25 mm; d1 = 10 mm, d2 = 10 mm



RFA-2

1544631


Aluminium flange adapter, rectangular, for solid shaft encoders with clamping flange; edge length 63.5 mm; 3 mm thick



RFA-13

1544642


Aluminium flange adapter, rectangular, for solid shaft encoders with clamping flange; edge length 80 mm; 4 mm thick



RFA-1

1544630


Aluminium flange adapter, rectangular, for solid shaft encoders with clamping flange; edge length 58 mm; 4 mm thick



RFA-4

1544633


Euro flange – aluminium flange adapter for solid shaft encoders, Ø 115 mm; reference diameter 100 mm; adapts 58 mm clamping flange to Euro flange



RFA-6

1544635


Aluminium flange adapter for solid shaft encoders with clamping flange, Ø 58 mm; adapts clamping flange to synchro flange



RFA-7

1544636


Aluminium flange adapter for solid shaft encoders, Ø 65 mm; adapts to Ø 65 mm flange and 48 mm reference diameter



RFA-8


1544637

Aluminium flange adapter for solid shaft encoders with clamping flange, Ø 70 mm; thickness 4 mm, adapts to Ø 70 mm flange



RFA-9


1544638



Aluminium angle flange for solid shaft encoders with Ø 58 mm clamping flange

RFA-11


1544640



Aluminium flange adapter for solid shaft encoders with clamping flange, Ø 70 mm; thickness 10 mm, adapts to Ø 70 mm flange

RFA-12

1544641



Aluminium flange adapter, rectangular, for solid shaft encoders with clamping flange; edge length 70 mm; 10 mm thick