


RI-10SA1R-2K3600-10MIL/N29

Incremental Shaft Encoder

Industrial Line



Features

- Square flange, Ø 63.5 mm
- Solid shaft, Ø 3/8" x 5/8"
- Optical measuring principle
- Shaft material, stainless steel
- Protection class IP67 on housing and shaft side
- -40...+85 °C
- Max. 6000 rpm (continuous operation 3000 rpm)
- 5...30 VDC
- Male connector MIL, 10-pole
- Push-pull 7272, with inverted signals
- Pulse frequency max. 300 kHz
- 3600 pulses per revolution

Technical data

Type	RI-10SA1R-2K3600-10MIL/N29
ID	200006486
Measuring principle	Optical
General data	
Max. Rotational Speed	6000 rpm
Moment of inertia of the rotor	$1.8 \times 10^{-6} \text{ kgm}^2$
Starting torque	< 0.05 Nm
Output type	Incremental
Resolution, incremental	3600 ppr
Electrical data	
Operating voltage	5...30 VDC
No-load current	100 mA
Output current	≤ 20 mA
Short-circuit protection	yes
Wire breakage/Reverse polarity protection	no
Pulse frequency max.	300 kHz
Signal level high	min. $U_b - 2 \text{ V}$
Signal level low	max. 0.5 V
Output function	Push-Pull 7272, with inverted signals
Mechanical data	
Design	Solid shaft
Flange type	Synchro flange
Flange diameter	Ø 63.5 mm


Technical data

Shaft Type	Solid shaft
Shaft material	Stainless steel
Housing material	Die-cast zinc
Electrical connection	Connector
	MIL, 10-pole
Axial shaft load	50 N
Radial shaft load	100 N
Environmental conditions	
Ambient temperature	-40...+85 °C
Vibration resistance (EN 60068-2-6)	300 m/s ² , 10...2000 Hz
Shock resistance (EN 60068-2-27)	3000 m/s ² , 6 ms
Protection class	IP67
Protection class shaft	IP67


Accessories

RFA-2
1544631



Aluminium flange adapter, rectangular, for solid shaft encoders with clamping flange; edge length 63.5 mm; 3 mm thick

RFA-13
1544642



Aluminium flange adapter, rectangular, for solid shaft encoders with clamping flange; edge length 80 mm; 4 mm thick

RFA-1
1544630



Aluminium flange adapter, rectangular, for solid shaft encoders with clamping flange; edge length 58 mm; 4 mm thick

RFA-4
1544633


Euro flange – aluminium flange adapter for solid shaft encoders, Ø 115 mm; reference diameter 100 mm; adapts 58 mm clamping flange to Euro flange

RFA-6
1544635



Aluminium flange adapter for solid shaft encoders with clamping flange, Ø 58 mm; adapts clamping flange to synchro flange

RFA-7
1544636


Aluminium flange adapter for solid shaft encoders, Ø 65 mm; adapts to Ø 65 mm flange and 48 mm reference diameter

RFA-8


1544637



Aluminium flange adapter for solid shaft encoders with clamping flange, Ø 70 mm; thickness 4 mm, adapts to Ø 70 mm flange

RFA-9


1544638



Aluminium angle flange for solid shaft encoders with Ø 58 mm clamping flange

RFA-11


1544640



Aluminium flange adapter for solid shaft encoders with clamping flange, Ø 70 mm; thickness 10 mm, adapts to Ø 70 mm flange

RFA-12

1544641



Aluminium flange adapter, rectangular, for solid shaft encoders with clamping flange; edge length 70 mm; 10 mm thick